





The photograph may not match the reference exactly. Please read the product description to identify the finish.



TECHNICAL CHARACTERISTICS

Type:	Downlight
IP Protection degrees:	IP44
IK Protection degrees:	IK06
Lampholder:	1 x G24d3
Power (W):	G24d3 26
Voltage / Frequency:	230V/50Hz
Warranty (Years):	2
Units per box:	12
Net Weight (Kg):	1.41
EAN:	8435111055625




MATERIALS / FINISHES

Structure material:	Injected aluminium	Diffuser material:	Glass
Structure finish:	Black	Diffuser finish:	Matt

GEAR


Gear included: Yes, Magnetic



Download photometric file .ldt /.ies

Luminaria		Ensayo		Lámpara	
Código	05-9179-34-B8	Código	05-9179-34-B8	Código	DULUX D 26W840
Nombre	Aplicador indir. 26W TC-D G24d3	Nombre	Aplicador indir. 26W TC-D G24d3	Número	1
Familia	- LEDS-C4	Fecha	11-11-2008	Posición	Universal
Eficiencia	16.07%	Sist. de Coord.	C-G	Flujo Total	1800.00 lm
Valor Máximo	98.32 cd/klm	Posición	C=90.00 G=35.00	Sim. en los planos	270-90

120mm x 265mm





Semiplanos C

270.0 ————


180.0 ———— 0.0

————— 90.0






ALUMINIO INYECTADO
INJECTED ALUMINUM




CAJA DE EMPOTRAR DE PP
PP FLUSH FITTING BOX

CAJA DE EMPOTRAR
FLUSH FITTING BOX


①



②



③



④

