BAP LED

design Alberto Meda / Paolo Rizzatto, 2011

LUCE PLAN

Type: Table

Light source LED 12W (*) 2700K
466 lm (delivered)
dimmable

Product use : Indoor

Materials : Aluminium body, glass-reinforced nylon head.

Colors: Structure in white or black

Description : Specifically designed to provide correct lighting when used with computer moni tors, the BAP with LED source guarantees the best colour temperature with a lower energy consumption. The slim and elegant head integrates a blue polycarbonate filter.

Insulation class:

Reference code : Structure D1 9L.LED
1D19LL000001 black
1D19LL000002 white

Table base D19 /1
1D19/1 N00001 black
1D19/1 N00002 white

Surface mount D19/2
1D19/2000001 black
1D19/2000002 white

Desk joint D19/8
1D19/8000001 black
1D19/8000002 white

Clamp D19/9
1D19/9000001 black
1D19/9000002 white

(*) The LED lamps cannot be changed in the luminaire
Power consumption by device

D19LED + D19/1



Isolux

head h 50cm
max Lux = 2191 lx



D19LED + D19/2



Isolux

head h 50cm
max Lux = 21 91 lx



D19 /8 desk joint



D19 /9 clamp



BAP LED

design Alberto Meda / Paolo Rizzatto, 2011

LUCE PLAN

Type: Table

Light source LED 12W (*) 2700K
466 lm (delivered)
dimmable

Product use : Indoor

Materials : Aluminium body, glass-reinforced nylon head.

Colors: Structure in white or black

Description : Specifically designed to provide correct lighting when used with computer moni tors, the BAP with LED source guarantees the best colour temperature with a lower energy consumption. The slim and elegant head integrates a blue polycarbonate filter.

Insulation class:

Reference code : Structure D1 9L.LED
1D19LL000001 black
1D19LL000002 white

Table base D19 /1
1D19/1 N00001 black
1D19/1 N00002 white

Surface mount D19/2
1D19/2000001 black
1D19/2000002 white

Desk joint D19/8
1D19/8000001 black
1D19/8000002 white

Clamp D19/9
1D19/9000001 black
1D19/9000002 white

(*) The LED lamps cannot be changed in the luminaire
Power consumption by device

D19LED + D19/1



Isolux

head h 50cm
max Lux = 2191 lx



D19LED + D19/2



Isolux

head h 50cm
max Lux = 21 91 lx



D19 /8 desk joint



D19 /9 clamp