



## Ballerup Mini

### Design:

C. J. Nørgaard Pedersen & P. Hougaard Nielsen

### Concept:

The light distribution is symmetric and directed downwards. The vertical three-layer mouth-blown glass cylinder provides a soft and comfortable light on the ceiling around the fixture, as well as reducing glare for passers-by.

### Finish:

White, powder coated. White opal glass.

### Material:

Diffuser: Mouth-blown white opal glass. Ring: Punched steel.

### Mounting:

Ceiling thickness: 5-32mm. Ceiling Cut-Out: Ø 105mm. Looping: Not approved. Driver hardwired to housing. For more information please look at [www.louis Poulsen.com](http://www.louis Poulsen.com).

### Weight:

Min: 0.6 kg Max: 3.3 kg

### Class:

Ingress protection IP20. Electric shock protection II.

### Info notes:

Supplied with light source. For LED replacement kits please do contact Louis Poulsen. The innovation of the LED technology is constant. The specifications mentioned are based on present technology. Please find updated info on products on our website [www.louis Poulsen.com](http://www.louis Poulsen.com)

## PRODUCT OVERVIEW

CCT/Watt/ Lumen	Light source	Finish	Lighting control	Efficacy	Order-no.
3000K 15.0 335	15W LED 3000K	WHT	DALI	22	5742586832

SPAREPART

Product name:	Ordering number:
BALLERUP MINI/MICRO, GLASS	5742560719