



---

## LP Charisma King

---

**Design:**

PLH design as

**Concept:**

The fixture emits a downward directed light. The two opal shades distribute a small amount of light laterally illuminating the fixture itself

**Finish:**

Aluminium coloured, wet painted or white, powder coated. Clear acrylic.

**Material:**

Cone: Injection moulded clear acrylic. Shades: Injection moulded opal polycarbonate. Reflector: Spun aluminium. Ring: Die cast aluminium. Housing: Spun aluminium. Struts: Die cast aluminium.

**Mounting:**

Suspension type: Cable 5x0,75mm<sup>2</sup> & wire. Canopy: Yes. Cable length: 4m.

**Weight:**

Min: 7.0 kg Max: 7.3 kg

**Class:**

Ingress protection IP20. Electric shock protection I w. ground.

**Info notes:**

The innovation of the LED technology is constant. The specifications mentioned are based on present technology. Please find updated info on products on our website [www.louispoulsen.com](http://www.louispoulsen.com).

## PRODUCT OVERVIEW

CCT/Watt/ Lumen	Light source	Finish	Reflector	Shade	Lighting control	Efficacy	Order-no.
3000K 39.0 3144	39W LED 3000K	GREY ALU COL	MEDIUM	OPAL PC	DALI	81	5741110953
3000K 39.0 3144	39W LED 3000K	WHT	MEDIUM	OPAL PC	DALI	81	5741110966

## SPAREPART

Product name:	Ordering number:
CANOPY BLACK 2-PART, TOPHAT ®	5749329021
CANOPY WHITE 2-PART, TOPHAT ®	5749329034