



LP Circle Recessed

Design:

Mikkel Beedholm/KHR arkitekter

Concept:

The fixture emits diffuse light via a high-efficiency acrylic diffuser. The diffuser, which is encircled by a voluminous coloured or white ring, is hidden when viewed from low angles. Angling the inner side of the ring 5° creates a comfortable and decorative graduation of the light from the diffuser. With two diameters and four different installation options, the lights series can be used for a wide range of applications.

Finish:

White, Black, Pale Petroleum or Yellow. Powder coated.

Material:

Reflector: Deep drawn aluminium. Diffuser: Acrylic, frosted. Installation lock: Polyamide.

Mounting:

Ceiling thickness: 1–40 mm. Driver is a separate unit (supplied with luminaire). Cut-out dimensions: Ø 260: Ø 248mm, Ø 450: Ø 438mm. Looping: Approved, max 5x1.5mm². For further information, visit www.louis Poulsen.com.

Weight:

Min: 2.2 kg Max: 5.0 kg

Class:

Ingress protection IP20. Electric shock protection I.

Info notes:

LED technology is constantly developing. The specifications given are based on existing technology. Please find updated info on products on our website www.louis Poulsen.com. For LED replacement kit please do contact Louis Poulsen. Please contact Louis Poulsen for the following versions: LP Circle Ø 450 HO: High output for projects with high ceilings or where high illumination is required. LP Circle Ø 450 with microprismatic diffuser for UGR <19 (CIE 117). If you have special requirements concerning colour temperature, IP class, emergency lighting solutions or other modifications to the LP Circle model, please contact Louis Poulsen.

Specification notes:

A separate LED driver is supplied with the fixture. All LED power measurements are measured as system power.

PRODUCT OVERVIEW

Dimensions	CCT/Watt/ Lumen	Light source	Finish	Shield/Diffuser	Lighting control	Efficacy	Order-no.
Ø 260	-	16W LED KELVIN ADJUSTABLE	WHT	OPAL	DALI KELVIN ADJUSTABLE	-	5742587543
Ø 260	3000K	13W LED 3000K	YELLOW	OPAL	DALI/SWITCH-DIM	-	5742582043
Ø 260	3000K	13W LED 3000K	PALE PETROLEUM	OPAL	DALI/SWITCH-DIM	-	5742582056
Ø 260	3000K 13.0 1086	13W LED 3000K	BLK	OPAL	DALI/SWITCH-DIM	84	5742582690
Ø 260	3000K 13.0 1342	13W LED 3000K	WHT	OPAL	DALI/SWITCH-DIM	103	5742582658
Ø 260	4000K 13.0 1386	13W LED 4000K	WHT	OPAL	DALI/SWITCH-DIM	107	5742582674
Ø 450	-	26W LED KELVIN ADJUSTABLE	WHT	OPAL	DALI KELVIN ADJUSTABLE	-	5742587569
Ø 450	3000K	25W LED 3000K	YELLOW	OPAL	DALI/SWITCH-DIM	-	5742582124
Ø 450	3000K	25W LED 3000K	PALE PETROLEUM	OPAL	DALI/SWITCH-DIM	-	5742582137
Ø 450	3000K 25.0 2281	25W LED 3000K	BLK	OPAL	DALI/SWITCH-DIM	91	5742583000
Ø 450	3000K 25.0 2626	25W LED 3000K	WHT	OPAL	DALI/SWITCH-DIM	105	5742582962
Ø 450	4000K 25.0 2712	25W LED 4000K	WHT	OPAL	DALI/SWITCH-DIM	108	5742582988

EMERGENCY LIGHTING

Product name:	Ordering number:
EMERGENCY PACK SIZE 3 LED-D 3H	5742579904
EMERGENCY PACK SIZE 3 LED-DA 3H	5742579917

SPAREPART

Product name:	Ordering number:
CIRCLE Ø260 DIFFUSER	5742583657
CIRCLE Ø450 DIFFUSER	5742583660