
# louis poulsen





# LP Circle Suspended

#### Design:

Mikkel Beedholm/KHR arkitekter

#### Concept:

The fixture emits diffuse light via a high-efficiency acrylic diffuser. The diffuser, which is encircled by a voluminous coloured or white ring, is hidden when viewed from low angles. Angling the inner side of the ring 5° creates a comfortable and decorative graduation of the light from the diffuser. Perforated body discreetly illuminates the other components of the fixture.

#### Finish:

White, Black, Pale Petroleum or Yellow. Powder coated.

#### Material:

Reflector: Deep drawn aluminium. Diffuser: Acrylic, frosted.

#### Mounting:

Hung: Cord 5x1.5mm2, 3m.

#### Weight:

Min: 2.6 kg Max: 5.9 kg

#### Class:

Ingress protection IP20. Electric shock protection I.

#### Info notes:

LED technology is constantly developing. The specifications given are based on existing technology. Please find updated info on products on our website www.louispoulsen.com. For LED replacement kit please do contact Louis Poulsen. Please contact Louis Poulsen for the following versions: LP Circle Ø 450 HO: High output for projects with high ceilings or where high illumination is required. LP Circle Ø 450 with microprismatic diffuser for UGR <19 (CIE 117). If you have special requirements concerning colour temperature, IP class, emergency lighting solutions or other modifications to the LP Circle model, please contact Louis Poulsen.

#### Specification notes:

The driver is built into the fixture All LED power measurements are measured as system power.

## PRODUCT OVERVIEW

#### CCT/Watt/

- Ø 260 Ø 260	3000К - 3000К	25W LED 3000K 16W LED KELVIN ADJUSTABLE	BLK WHT	- OPAL	-	-	DALI/SWITCH-DIM	-	5741106886	
	- 3000K		WHT	OPAL						
Ø 260	3000К	ADJUSTABLE			NOT	NOT	DALI KELVIN	- 5741098208		
Ø 260	3000K				APPLICABLE	APPLICABLE	ADJUSTABLE		5741098208	
Ø 260	3000К	13W LED 3000K	WHT	OPAL	NOT	NOT	DALI/SWITCH-DIM	- 5741094888	5741004999	
					APPLICABLE	APPLICABLE			5741094886	
Ø 260	3000К	13W LED 3000K	PALE	OPAL	WHT TEX	SUSPENDED	DALI/SWITCH-DIM	- 5741095573		
			PETROLEUM							
Ø 260	3000K	13W LED 3000K	YELLOW	OPAL	WHT TEX	SUSPENDED	DALI/SWITCH-DIM	-	5741095586	
Ø 260	3000K	13W LED 3000K	BLK	OPAL	NOT	NOT	DALI/SWITCH-DIM		5741000770	
					APPLICABLE	APPLICABLE			5741099773	
Ø 260	3000K 13.0 107	213W LED 3000K	BLK	OPAL	NOT	NOT	DALI/SWITCH-DIM	82 574109716	5741007100	
					APPLICABLE	APPLICABLE			5/4109/160	
Ø 260	3000K 13.0 133	313W LED 3000K	WHT	OPAL	NOT	NOT	DALI/SWITCH-DIM	103 574109714	5741007144	
					APPLICABLE	APPLICABLE			5741097144	
Ø 260	4000K 13.0 137	713W LED 4000K	WHT	OPAL	NOT	NOT	DALI/SWITCH-DIM	106	5741007157	
					APPLICABLE	APPLICABLE			5741097157	
Ø 450	-	26W LED KELVIN	WHT	OPAL	NOT	NOT	DALI KELVIN	-	5741008211	
		ADJUSTABLE			APPLICABLE	APPLICABLE	ADJUSTABLE		5741098211	
Ø 450	3000К	25W LED 3000K	WHT	OPAL	NOT	SUSPENDED	DALI/SWITCH-DIM		5741094891	
					APPLICABLE				5741054091	
Ø 450	3000К	25W LED 3000K	PALE	OPAL	WHT TEX	SUSPENDED	DALI/SWITCH-DIM	-	5741095654	
			PETROLEUM							
Ø 450	3000K	25W LED 3000K	YELLOW	OPAL	WHT TEX	SUSPENDED	DALI/SWITCH-DIM	-	5741095667	
Ø 450	3000K	25W LED 3000K	BLK	OPAL	NOT	SUSPENDED	DALI/SWITCH-DIM		5741000796	
					APPLICABLE				5741099786	

### **SPAREPART**

Product name:

Ordering number:

CIRCLE Ø450 DIFFUSER

5742583660