



SET LOCATION - KEA

## LP Slim Round Semi Recessed

### Design:

Louis Poulsen A/S

### Concept:

The slim housing encircles and high-efficient acrylic diffuser emitting diffused primarily downward directed light. The slim body has a slight curvature and an inner curve which reduces contrast. The product family comes in a range of sizes and mounting options for a wide range of applications. Surface mounted and suspended versions have an indirect light component.

### Finish:

White, aluminium grey or black, powder coated.

### Material:

Reflector: Die cast aluminium. Diffuser: Acrylic, opal. Installation lock: Aluminium.

### Mounting:

Ceiling thickness: 1-60 mm. Cut-out dimensions: Ø 250: Ø194mm, Ø 440: Ø194mm, Ø 680: Ø 266mm. Optional mounting bracket or wire for alternative installation. Looping: Approved, max 5x1.5mm<sup>2</sup>. Driver integrated. For wall mounting please use diffuser springs (accessory).

### Weight:

Max: 9.7 kg

### Class:

Ingress protection IP20. Electric shock protection I.

PRODUCT OVERVIEW

Dimensions		CCT/Watt/ Lumen	Light source	Finish	Shield/Diffuser	Mounting	Lighting control	Efficacy	Order-no.
Ø 250	-		16W LED KELVIN ADJUSTABLE	WHITE	OPAL	SEMI-RECESSED DALI	KELVIN ADJUSTABLE	-	5742584258
Ø 250	3000K 13.0 1089	13W	LED 3000K	BLACK	OPAL	SEMI-RECESSED DALI		84	5742584261
Ø 250	3000K 13.0 1131	13W	LED 3000K	ALU GREY	OPAL	SEMI-RECESSED DALI		87	5742584274
Ø 250	3000K 13.0 1248	13W	LED 3000K	WHITE	OPAL	SEMI-RECESSED DALI		96	5742584232
Ø 250	4000K 13.0 1274	13W	LED 4000K	WHITE	OPAL	SEMI-RECESSED DALI		98	5742584245
Ø 440	-		26W LED KELVIN ADJUSTABLE	WHITE	OPAL	SEMI-RECESSED DALI	KELVIN ADJUSTABLE	-	5742584313
Ø 440	3000K 25.0 2373	25W	LED 3000K	BLACK	OPAL	SEMI-RECESSED DALI		95	5742584326
Ø 440	3000K 25.0 2454	25W	LED 3000K	ALU GREY	OPAL	SEMI-RECESSED DALI		98	5742584339
Ø 440	3000K 25.0 2677	25W	LED 3000K	WHITE	OPAL	SEMI-RECESSED DALI		107	5742584290
Ø 440	4000K 25.0 2731	25W	LED 4000K	WHITE	OPAL	SEMI-RECESSED DALI		109	5742584300
Ø 680	3000K 53.0 5814	54W	LED 3000K	BLACK	OPAL	SEMI-RECESSED DALI		110	5742584384
Ø 680	3000K 53.0 5944	54W	LED 3000K	ALU GREY	OPAL	SEMI-RECESSED DALI		112	5742584397
Ø 680	3000K 53.0 6266	54W	LED 3000K	WHITE	OPAL	SEMI-RECESSED DALI		118	5742584355
Ø 680	4000K 53.0 6393	54W	LED 4000K	WHITE	OPAL	SEMI-RECESSED DALI		121	5742584368