



LP Slim Round Surface Mounted

Design:

Louis Poulsen A/S

Concept:

The slim housing encircles and high-efficient acrylic diffuser emitting diffused primarily downward directed light. The slim body has a slight curvature and an inner curve which reduces contrast. The product family comes in a range of sizes and mounting options for a wide range of applications. Surface mounted and suspended versions have an indirect light component.

Finish:

White, aluminium grey or black, powder coated.

Material:

Reflector: Die cast aluminium. Diffuser: Acrylic, opal. Installation lock: Aluminium.

Mounting:

Directly on ceiling. Looping: Approved, max 5x1.5mm². Cable entries: Rear, Side-mounted. Driver integrated. For wall mounting please use enclosed diffuser springs.

Weight:

Min: 1.8 kg Max: 9.8 kg

Class:

Ingress protection IP20. Electric shock protection I.

PRODUCT OVERVIEW

Dimensions	CCT/Watt/ Lumen	Light source	Finish	Shield/Diffuser	Mounting	Lighting control	Efficacy	Order-no.
-	-	KELVIN ADJUSTABLE	WHITE	-	-	DALI KELVIN ADJUSTABLE	-	5742584180
Ø 250	-	16W LED KELVIN ADJUSTABLE	WHITE	OPAL	SURFACE MOUNTED DALI	KELVIN ADJUSTABLE	-	5742584067
Ø 250	3000K 13.0 1092	13W LED 3000K	BLACK	OPAL	SURFACE MOUNTED DALI		84	5742584070
Ø 250	3000K 13.0 1142	13W LED 3000K	ALU GREY	OPAL	SURFACE MOUNTED DALI		88	5742584083
Ø 250	3000K 13.0 1254	13W LED 3000K	WHITE	OPAL	SURFACE MOUNTED DALI		96	5742584041
Ø 250	4000K 13.0 1279	13W LED 4000K	WHITE	OPAL	SURFACE MOUNTED DALI		98	5742584054
Ø 440	-	26W LED KELVIN ADJUSTABLE	WHITE	OPAL	SURFACE MOUNTED DALI	KELVIN ADJUSTABLE	-	5742584122
Ø 440	3000K 25.0 2404	25W LED 3000K	BLACK	OPAL	SURFACE MOUNTED DALI		96	5742584135
Ø 440	3000K 25.0 2478	25W LED 3000K	ALU GREY	OPAL	SURFACE MOUNTED DALI		99	5742584148
Ø 440	3000K 25.0 2659	25W LED 3000K	WHITE	OPAL	SURFACE MOUNTED DALI		106	5742584106
Ø 440	4000K 25.0 2713	25W LED 4000K	WHITE	OPAL	SURFACE MOUNTED DALI		109	5742584119
Ø 680	3000K 53.0 5861	54W LED 3000K	BLACK	OPAL	SURFACE MOUNTED DALI		111	5742584193
Ø 680	3000K 53.0 5978	54W LED 3000K	ALU GREY	OPAL	SURFACE MOUNTED DALI		113	5742584203
Ø 680	3000K 53.0 6262	54W LED 3000K	WHITE	OPAL	SURFACE MOUNTED DALI		118	5742584164
Ø 680	4000K 53.0 6389	54W LED 4000K	WHITE	OPAL	SURFACE MOUNTED DALI		121	5742584177