



LP Slim Round Suspended

Design:

Louis Poulsen A/S

Concept:

The slim housing encircles and high-efficient acrylic diffuser emitting diffused primarily downward directed light. The slim body has a slight curvature and an inner curve which reduces contrast. The product family comes in a range of sizes and mounting options for a wide range of applications. Surface mounted and suspended versions have an indirect light component.

Finish:

White, aluminium grey or black, powder coated.

Material:

Reflector: Die cast aluminium. Diffuser: Acrylic, opal. Installation lock: Aluminium.

Mounting:

Suspension: Cord 2x0.75 mm², 5m. Driver integrated in canopy.

Weight:

Max: 9.6 kg

Class:

Ingress protection IP20. Electric shock protection I.

PRODUCT OVERVIEW

CCT/Watt/		Cable					Efficacy	Order-no.
Dimensions	Lumen	Light source	Finish	Shield/Diffuser	type	Mounting		
Ø 250	-	16W LED KELVIN ADJUSTABLE	WHITE	OPAL	WHT PL	SUSPENDED DALI ADJUSTABLE	-	5741099553
Ø 250	3000K 13.0 1092	13W LED 3000K	BLACK	OPAL	BLK PL	SUSPENDED DALI	84	5741099566
Ø 250	3000K 13.0 1142	13W LED 3000K	ALU GREY	OPAL	WHT PL	SUSPENDED DALI	88	5741099579
Ø 250	3000K 13.0 1254	13W LED 3000K	WHITE	OPAL	WHT PL	SUSPENDED DALI	96	5741099537
Ø 250	4000K 13.0 1279	13W LED 4000K	WHITE	OPAL	WHT PL	SUSPENDED DALI	98	5741099540
Ø 440	-	26W LED KELVIN ADJUSTABLE	WHITE	OPAL	WHT PL	SUSPENDED DALI ADJUSTABLE	-	5741099618
Ø 440	3000K 25.0 2404	25W LED 3000K	BLACK	OPAL	BLK PL	SUSPENDED DALI	96	5741099621
Ø 440	3000K 25.0 2478	25W LED 3000K	ALU GREY	OPAL	WHT PL	SUSPENDED DALI	99	5741099634
Ø 440	3000K 25.0 2659	25W LED 3000K	WHITE	OPAL	WHT PL	SUSPENDED DALI	106	5741099595
Ø 440	4000K 25.0 2713	25W LED 4000K	WHITE	OPAL	WHT PL	SUSPENDED DALI	109	5741099605
Ø 680	-	KELVIN ADJUSTABLE	WHITE	OPAL	WHT PL	SUSPENDED DALI ADJUSTABLE	-	5741099676
Ø 680	3000K 53.0 5861	54W LED 3000K	BLACK	OPAL	BLK PL	SUSPENDED DALI	111	5741099689
Ø 680	3000K 53.0 5978	54W LED 3000K	ALU GREY	OPAL	WHT PL	SUSPENDED DALI	113	5741099692
Ø 680	3000K 53.0 6262	54W LED 3000K	WHITE	OPAL	WHT PL	SUSPENDED DALI	118	5741099650
Ø 680	4000K 53.0 6389	54W LED 4000K	WHITE	OPAL	WHT PL	SUSPENDED DALI	121	5741099663