



## Oslo Mini

### Design:

Kurt Nørregaard

### Concept:

The fixture emits a narrow band of light directed downwards. The reflector rings direct a small amount of light towards the ceiling, creating a soft, harmonic transition between the fixture and ceiling. They also reduce the angle of glare, minimizing any annoyance to passers-by.

### Finish:

White, powder coated.

### Material:

Shades: Spun steel and aluminium.

### Mounting:

Ceiling thickness: 5-32mm. Ceiling Cut-Out: Ø 105mm. Terminal block: 1x2x4mm<sup>2</sup>. Looping: Not approved. Driver hardwired to housing. For more information please look at [www.louis Poulsen.com](http://www.louis Poulsen.com).

### Weight:

Min: 0.6 kg Max: 3.3 kg

### Class:

Ingress protection IP20. Electric shock protection II.

### Info notes:

Supplied with light source. For LED replacement kits please do contact Louis Poulsen. The innovation of the LED technology is constant. The specifications mentioned are based on present technology. Please find updated info on products on our website [www.louis Poulsen.com](http://www.louis Poulsen.com)

## PRODUCT OVERVIEW

CCT/Watt/ Lumen	Light source	Finish	Lighting control	Efficacy	Order-no.
3000K 15.0 555	15W LED 3000K	WHT	DALI	37	5742586816