



PH 5-4¹/₂ & PH 6¹/₂-6

Design:

Ebbe Christensen & Sophus Frandsen, Poul Henningsen

Concept:

The trumpet-shaped top shade on the fixture provides illumination of the area above the three shades, which primarily direct the light downwards. A base reflector and a blue glare ring protect against glare from all angles. The strongest light is directly under the fixture. The shades have a matt white painted finish to ensure very comfortable lighting.

Finish:

White.

Material:

Shades: Spun aluminium. Anti-glare disc: Blue, spun aluminium. Struts: Rolled aluminium coloured.

Mounting:

Suspension type: PH 5-4¹/₂: Cable 3 x 0,75mm² & Wire. Canopy: Yes. Cable length: 3m. PH 6¹/₂-6: Cable 2 x 0.75 mm² and wire. Canopy or external driver box contains driver. Cable length: 4m. Maximum distance between external driver box and fixture: 20m.

Weight:

Min: 2.4 kg Max: 9.5 kg

Class:

Ingress protection IP20. Electric shock protection I w. ground.

Info notes:

The LED insert fits as standard PH 6¹/₂-6 E27/E40 produced after 1999. For PH 6¹/₂-6 produced prior to 1999 you need a renovation kit which can be acquired as an accessory. Please note the LED insert does not fit variants produced with metal halide. For LED replacement kits please do contact Louis Poulsen. The innovation of the LED technology is constant. The specifications mentioned are based on present technology. Please find updated info on products on our website www.louis Poulsen.com

Specification notes:

200W E27 only available for PH 5-4¹/₂. The innovation of light sources is ongoing. Consequently we only inform about the max. wattages. On www.louis Poulsen.com we update a list of recommendable light sources.

PRODUCT OVERVIEW

Dimensions	CCT/Watt/ Lumen	Light source	Finish	Cable type	Lighting control	Plug	Efficacy	Order-no.
-	2700K	96W LED 2700K	WHT	-	DIM 1-10V	-	-	5741096488
-	2700K	96W LED 2700K	WHT	-	DIM 1-10V	-	-	5741096747
-	3000K	96W LED 3000K	WHT	-	DIM 1-10V	-	-	5741096501
-	3000K	96W LED 3000K	WHT	-	DIM 1-10V	-	-	5741096763
5-4½	-	1X200W E27	WHT	WHT TEX	NONE	NOT APPLICABLE	-	5741085868
6½-6	2700K 96.0 4686	96W LED 2700K	WHT	WHT TEX/WIRE	DALI	INT. DRIVER	49	5741094943
6½-6	2700K 96.0 4686	96W LED 2700K	WHT	WHT TEX/WIRE	DALI	EXT. DRIVER	49	5741094969
6½-6	2700K 96.0 4686	96W LED 2700K	WHT	WHT TEX/WIRE	WIRELESS BLUETOOTH	INT. DRIVER	49	5741094985
6½-6	3000K 96.0 4875	96W LED 3000K	WHT	WHT TEX/WIRE	DALI	INT. DRIVER	51	5741094956
6½-6	3000K 96.0 4875	96W LED 3000K	WHT	WHT TEX/WIRE	DALI	EXT. DRIVER	51	5741094972
6½-6	3000K 96.0 4875	96W LED 3000K	WHT	WHT TEX/WIRE	WIRELESS BLUETOOTH	INT. DRIVER	51	5741094998

SPAREPART

Product name:	Ordering number:
CANOPY WHITE 2-PART, TOPHAT ®	5749329034

ACCESSORIES

Product name:	Ordering number:
PH 6½-6 PEN RENOVATION KIT SUSP BEFORE99	5741097050

SUSPENSION

Product name:	Ordering number:
PH 6½-6 SUSP-KIT LED-DA 27K90 INT/DRV	5741110979
PH 6½-6 SUSP-KIT LED-DA 3K90 INT/DRV	5741110982
PH 6½-6 SUSP-KIT LED-DA 27K90 EXT/DRV	5741110995
PH 6½-6 SUSP-KIT LED-DA 3K90 EXT/DRV	5741111004
PH 6½-6 SUSP-KIT LED-WB 27K90 INT/DRV	5741111017
PH 6½-6 SUSP-KIT LED-WB 3K90 INT/DRV	5741111020