louis poulsen





PH 80

Design:

Poul Henningsen

Concept:

The fixture emits diffuse and symmetrical light. The majority of the light is directed downwards, and the opal acrylic shades provide comfortable room lighting. The red hue of the top reflector helps giving the light a warmer glow.

Finish:

White opal acrylic. High lustre chrome plated.

Material:

Shades: High pressure moulded white opal acrylic. Top shade: Black, high pressure moulded polycarbonate. Base: Black, high pressure moulded ABS. Stem: High lustre chrome plated, steel.

Mounting:

Cable type: Plastic cord with plug. Cable length: 2.6m. Light control: On/off switch on cord.

Weight:

Min: 7.5 kg Max: 7.6 kg

Class:

Ingress protection IP20. Electric shock protection II w/o ground.

Specification notes:

The innovation of light sources is ongoing. Consequently we only inform about the max. wattages. On www.louispoulsen.com we update a list of recommendable light sources.

PRODUCT OVERVIEW

Light source	Finish	Switch/Plug	Order-no.
1X100W E27	WHT OPAL ACRYL	W/ON/OFF SWITCH	5744610816

SPAREPART

Product name:	Ordering number:
PH 80, TOP SHADE	5744610298
PH 80, MIDDLE SHADE	5744610638
PH 80, LOWER SHADE	5744610641
PH 80, SOCKET COVER W/BRANCH	5744610654
PH 80, TOP ROUGE/BLACK	5744610667
PH 80 FLOOR, REBUILDING SET	5744610793