



Riples

Design:

Jakob Wagner

Concept:

The fixture emits diffused light. The front consists of a concave clear front with ripples like rings in water. The ripples refract light in the front, creating a subtle change of appearance depending on the viewing angle. The concave form outlines the refracting, creating a higher intensity light towards the center, fading off toward the edges. A diffuser offset sits deep in the fixture, creating a sense of depth in the front. A slim housing creates the appearance of a floating disk, while perforations in the opaque housing allow indirect light to create a halo around the fixture.

Finish:

White opal diffuser and clear reflective front. Satin matt white.

Material:

Rear housing: Injection molded polycarbonate. Diffuser: Opalescent PMMA. Clear front: Clear UV resistant polycarbonate.

Mounting:

Terminal strip: 1x5x2.5mm². Cable access: 2 rear, Ø19mm or side mounting. Prepared for looping: Approved, max. 5x1.5mm².

Weight:

Min: 1.6 kg Max: 3.6 kg

Class:

Ingress protection IP20. Electric shock protection I.

Info notes:

Please contact Louis Poulsen for Switch-DIM, Wireless bluetooth control, other colour temperatures, Kelvin adjustable or LED replacement kit.

PRODUCT OVERVIEW

Dimensions	CCT/Watt/ Lumen	Light source	Finish	Mounting	Lighting control	Efficacy	Order-no.
Ø 310	3000K 13.0 1060	13W LED 3000K	OPAL	WALL & CEILING	DALI	82	5743141014
Ø 310	3000K 13.0 1060	13W LED 3000K	OPAL	WALL & CEILING	MOTION SENSOR	82	5743147050
Ø 500	3000K	25W LED 3000K	OPAL	WALL & CEILING	DALI	-	5743141030
Ø 500	3000K	25W LED 3000K	OPAL	WALL & CEILING	MOTION SENSOR	-	5743147063
Ø 500	3000K	25W LED 3000K	OPAL	WALL & CEILING	EMERG LIGHT 3 H	-	5743147076