



VL38 Table

Design:

Vilhelm Lauritzen

Concept:

The fixture emits downward directed light. The angle of the shade can be adjusted to optimize light distribution. The shade is painted white on the inside to ensure a soft comfortable light.

Finish:

Brushed brass. Black or White, powder coated.

Material:

Base: Die cast aluminium Shade: Spun aluminium. Stem: Brushed brass.

Mounting:

Cable type: Plastic cord. Cable length: 3,3m. Light control: Switch in the lamp stand. 2 light levels. Timer function: 4 hours/8 hours. LED driver: separate, plugs into power outlet.

Weight:

Min: 1.0 kg Max: 1.0 kg

Class:

Ingress protection IP20. Electric shock protection II w/o ground.

Info notes:

Function to set a fixed light level each time the lamp is connected to main power. LED driver fitted externally on cord. Two light levels 50% or 100%. Timer function to automatically turn off the light after amount of time, selectable between off/4 hours/8 hours. Adjustable (up and down) lamp shade. For LED replacement kit please contact Louis Poulsen. The innovation of the LED technology is constant. The specifications mentioned are based on present technology. Please find updated info on products on our website www.louispoulsen.com.

PRODUCT OVERVIEW

CCT/Watt/ Lumen	Light source	Finish	Efficacy	Order-no.
2700K 9.6 416	10W LED 2700K	WHITE	43	5744162322
2700K 9.6 416	10W LED 2700K	BLACK	43	5744163211

SPAREPART

Product name:	Ordering number:
ADAPTOR 12V BLK	5744164867
ADAPTOR 12V WHT	5744164870