



VL38 Wall

Design:

Vilhelm Lauritzen

Concept:

The fixture emits downward directed light. The angle of the shade can be adjusted to optimize light distribution. The shade is painted white on the inside to ensure a soft comfortable light.

Finish:

Brushed brass. Black or White, powder coated.

Material:

Wall box: Punched aluminium. Shade: Spun aluminium. Arm: Brushed brass.

Mounting:

Cable type: Plastic cord. Cable length: 3,3m. Light control: Switch on wall box. 2 light levels. Timer function: 4 hours/8 hours. LED driver: integrated in wall box.

Weight:

Min: 1.1 kg Max: 1.1 kg

Class:

Ingress protection IP20. Electric shock protection II w/o ground.

Info notes:

Function to set a fixed light level each time the lamp is connected to main power. LED driver integrated in wall box. Two light levels 50% or 100%. Timer function to automatically turn off the light after amount of time, selectable between off/4 hours/8 hours. Adjustable (up and down) and rotating (to the side) lamp shade. For LED replacement kit please contact Louis Poulsen. The innovation of the LED technology is constant. The specifications mentioned are based on present technology. Please find updated info on products on our website www.louis Poulsen.com.

PRODUCT OVERVIEW

CCT/Watt/ Lumen	Light source	Finish	Shade	Efficacy	Order-no.
-	-	-	-	-	10000141309
-	-	-	-	-	10000141310
2700K 9.6 416	10W LED 2700K	BLACK	TILTABLE/ROTATABLE	43	5743163393
2700K 9.6 416	10W LED 2700K	WHITE	TILTABLE/ROTATABLE	43	5743163429

SPAREPART

Product name:

Ordering number:

ADAPTOR 12V WHT

5744164870