louis poulsen



Yuh Wall

Design:

GamFratesi

Concept:

The fixture primarily provides direct glare-free downward directed light. The angle of the shade can be adjusted to optimize light distribution. A slim opening in the top of the shade provides soft, ambient upward illumination. A mechanical system provides great freedom of movement, so the light can always be set in the ideal position in the workspace, living room etc. Build-in LED technology provides a high quality of light with stepless dimming at 15 to 100%. Timer function to automatically turn off the light after amount of time, selectable between off/4 hours/8 hours. Function to set a fixed light level each time the lamp is connected to main power. The switch and dimmer button is placed on the wall box.

Finish:

White or black. Matt wet painted.

Material

Shade and wall box: Die cast aluminium. Stem: Extruded brass.

Mounting:

Cable type: Plastic cord. Cable length: 2,5m. Stepless dim between 15 and 100%. Timer function: 4 hours/8 hours. Light control: Switch on the wall box. LED Driver: integrated in the wall box.

Weight:

Min: 2.2 kg Max: 2.2 kg

Class:

Ingress protection IP20. Electric shock protection II w/o ground.

Info notes:

A single push button located at the lamp will control the functions on/off and dimming. Turn on/off the light with light fading in/out. Stepless dim of the light to a suitable level between 15 and 100%. Timer function to automatically turn off the light after amount of time, selectable between off/4 hours/8 hours. Function to set a fixed light level each time the lamp is connected to main power. LED driver integrated in wall box. For LED replacement kit please contact Louis Poulsen. The innovation of the LED technology is constant. The specifications mentioned are based on present technology. Please find updated info on products on our website www.louispoulsen.com.

PRODUCT OVERVIEW

CCT/Watt/ Lumen	Light source	Finish	Efficacy	Order-no.
-	-	-	-	10000141311
	-	-	-	10000141312
2700K 10.0 446	10W LED 2700K	BLACK	45	5743141409
2700K 10.0 446	10W LED 2700K	WHITE	45	5743143193