



## Ray Floor 2

by Rodolfo Dordoni , 2006



Floor lamp providing diffused lighting. Steel tube structure, welded, brushed and chrome-plated. Diffuser support in die-cast, polished and chrome-plated Zamak alloy. Injection-molded PA6 (nylon) lamp-cover. Color: white. Injection-molded PC (polycarbonate) inner diffuser. Color: 3% opal. Injection-molded elastic PVC (polyvinylchloride) feet. Lathe-shaped aluminum diffusers, painted white on the inside, and shiny white or black on the outside or gray-colored, blown and overlaid glass with glossy external finish. On the cable there is the electronic dimmer which allows the regulation of light brightness.



Mounting	Floor
Environment	Indoor
Finish	White, Glass, Black
Weight	6.2 (met) - 9.2 (glass) Kg
Light sources available	1 x HSGS E27 205W 3000K Halolux Ceram.Eco 4200lm - RF19973 1 x LED E27 21W 3000K 2452lm - RF25315
Emergency	Without
Switching	On the cable there is the electronic dimmer which allows the regulation of light brightness with a dial.
Voltage	220/240
Power	MAX 250W
Battery	No
Supply included	Yes
Cord Length	1900 mm
Materials	Aluminum, Glass, Steel
Colors	<div>● F5921030 - Black</div> <div>● F5921009 - White</div> <div>● F5920020 - Glass</div>