

KTribe Table 2

by Philippe Starck , 2007



Table luminaire providing diffused lighting. Base, rod support and diffuser support in diecast, polished and chrome-plated Zamak alloy. Base cover in black injection-molded PA (Nylon). Injection-molded PC (polycarbonate) opal inner diffuser. Outer diffusers in transparent or fumée PMMA (polymethylmethacrylate), and silver or bronze on the inner surface, by vacuum aluminum coating. Injection-molded PC (polycarbonate) upper ring, completely transparent or transparent diffuser and silver diffuser) or transparent brown for the outer bronze diffuser.



Mounting	Table
Environment	Indoor
Finish	Aluminized bronze, Aluminized silver, Fabric, Fumée, Transparent
Weight	5.9 Kg
Light sources available	1 x HSGS E27 150W 2900K 2870lm - RF20358 1 x LED E27 21W 3000K 2452lm - RF25315
Emergency	Without
Voltage	220/240
Power	150W
Battery	No
Supply included	Yes
Cord Length	1640 mm
Materials	Aluminum, Polycarbonate, Polymethylmethacrylate
Colors	<ul style="list-style-type: none"> F63030 - Fabric F6303000 - Transparent F6303004 - Aluminized silver F6303046 - Aluminized bronze F6303030 - Fumée

KTribe Table 1

by Philippe Starck , 2007



Table luminaire providing diffused lighting. Base, rod support and diffuser support in die-cast, polished Zamak alloy. Polished aluminum tubular. Injection-molded, matte black PA (Nylon) base cover. Injection-molded PC (polycarbonate) opal inner diffuser. Outer diffuser in transparent or fumée PMMA (polymethylmethacrylate).



Mounting	Table
Environment	Indoor
Finish	Fumée, Transparent
Weight	3.1 Kg
Light sources available	1 x HSGS E27 70W 2800K 1180lm - RF20405 1 x LED E27 21W 3000K 2452lm - RF25315
Emergency	Without
Switching	On the cable there is a traditional dimmer which allows the regulation of light.
Voltage	220-240V
Power	100W
Battery	No
Supply included	Yes
Cord Length	1640 mm
Materials	Aluminum, Methacrylate, Polycarbonate
Colors	<ul style="list-style-type: none"> F6263000 - Transparent F6263030 - Fumée

KTribe Table 1 Glass

by Philippe Starck , 2007



Table luminaire providing diffused lighting. Base, rod support and diffuser support in die-cast, polished Zamak alloy. Polished aluminum tubular. Injection-molded, matte black PA (Nylon) base cover. Injection-molded PC (polycarbonate) opal inner diffuser. Outer diffuser in transparent glass



Mounting	Table
Environment	Indoor
Finish	Transparent glass
Weight	4.6 Kg
Light sources available	1 x HSGS E27 70W 2800K 1180lm - RF20405 1 x LED E27 21W 3000K 2452lm - RF25315
Emergency	Without
Switching	On the cable there is a traditional dimmer which allows the regulation of light.
Voltage	220-240V
Power	100W
Battery	No
Supply included	Yes
Cord Length	1640 mm
Materials	Aluminum, Glass, Polycarbonate
Colors	 F6281000 - Transparent