



Chair.  
Legs in extruded aluminium polished. Seat  
and back in die-cast aluminium polished.

Please note: flame-retardant

— Complete with felt pads.

**SD834** polished

	Kg	6,20	m³	0,079 (0,82x0,52x0,18)	
		4,70		9401.79.00	

**SD834A** Assembled version.  
Fixed supplement (net)

	Kg	11,90	m³	0,18 (0,43x0,43x0,98)	
		4,70		9401.79.00	

Chair.  
Legs in extruded aluminium painted. Seat  
and back in die-cast aluminium painted.  
! Suitable for outdoor use.

Please note: flame-retardant

— Complete with felt pads.

**SD840** Colours (legs, seat and back):  
black 5130  
red-purple  
sand beige

news  
news

	Kg	6,20	m³	0,079 (0,82x0,52x0,18)		
		4,70		9401.79.00		

**SD840A** Assembled version.  
Fixed supplement (net)

	Kg	11,90	m³	0,18 (0,43x0,43x0,98)		
		4,70		9401.79.00		

Mirror, go to page > **339**

Stools, go to page > **142**

Tables, go to page > **252**

! As die-cast aluminium is not treated with any chemical products or any kind of painting, small marks or irregularities, which might be visible on the surface, should not be considered as faults, but on the contrary as technical results of the nature of aluminium itself. We recommend using specific cleaning products for aluminium. Aluminium is very likely to dull while using. Regular care is therefore necessary to maintain its original appearance.

**Test:**

ANSI/BIFMA X5.1-2011  
Leg sideways static load test UNI 10977/2002, L5  
Seat and back static load test UNI 10977/2002, L5  
Seat impact test UNI 10977/2002, L5

Leg forward static load test UNI 10977/2002, L5  
Seat and back fatigue test UNI 10977/2002, L4  
Seat front edge fatigue test UNI 10977/2002, L5  
Stability EN 1022:2005