

SPILLO

Marco Pagnoncelli - 2012

Lampada incasso a filo muro da parete e soffitto con doppia asta orientabile realizzata in trafilata di ottone sezione 7x7mm. Disponibile in varie altezze e diverse potenze. Illuminazione a microstriscia LED ad alta efficienza luminosa.

Necessita di alimentatore e controcassa, non inclusi.*

Finiture colore: verniciato bianco (BI), verniciato nero (NE), cromo (CR), oro opaco (OR).

Alimentatori, controcasse e specifiche tecniche a pag. 38-39.

Classe energetica A++, A+, A

Modello depositato

Built-in flush wall or ceiling lamp with double adjustable drawn brass rod, 7x7 mm section.

Available in various dimensions and power levels. Lighting by high luminous efficiency LED micro-strip. **Requires power supply unit and wall housing, which is not included.***

Available in: white varnish (BI), black varnish (NE), chrome (CR), brushed gold (OR).

Power adapters, wall housing and technical specifications on page 38-39.

Energy class A++, A+, A


Registered design

BI

NE

CR

OR



Art.	W	V	Lumen	°K led	A cm	B cm	C cm	D cm	E cm	Ø7 cm
SPILLO2i.50	9,24	12	770	3000	21,5	51,5	75	3,3	3	8,2x75,6
SPILLO2i.80	14,52	12	1210	3000	31,5	81,5	115	3,3	3	8,2x115,6

**LED
12V CRI90**

LED Disponibili a richiesta nella temperatura colore 2700 °K