




ALABAMA S-LIGHT SQUARE

PRODUCT SHEET



REF. 10194

FEATURES

IP: 33

Installation: Surface

High: 80 mm

Light Direction: Fixed

Minimum distance to lightened objects: 0.5 m

Lamps : LED

Protection class: Class I

Indirect light: Optional

* not included

LED MODULES

Energy efficiency : A+

Driver: Included

Life time: 50.000h

LED working constant current: 700mA

Color rendering current: CRI ≥80

LED Guarantee: 5 years

REF		3000K/4000K
10194.11		36,4 W 3920/4000 lm
10194.12		54,6 W 5880/6000 lm
10194.13		72,8 W 7840/8000 lm
10194.14		91 W 9800/10000 lm


FINISH

ALUMINUM 9005	WHITE RAL 9003	ANODIZED ALUMINUM	SILVER LEAF	GOLD LEAF	GOLD RAL 1036
BLUE RAL 5022	AQUA RAL 5021	GREEN RAL 6018	RED RAL 3000	FLAMINGO RAL 3018	PINK RAL 3014
ORANGE RAL 2004					

OPTIC COVER



☐ OPAL



☐ MICROPRISMATIC

DIMMABLE OPTIONS


☐ 1.10V

☐ PUSH

☐ DALI

OPTIONAL

Distance from lighting item to ceiling in **indirect light** option





Date: _____

Company: _____

Project: _____

Quantity: _____

Features: _____



Partida Madrigueres Sud 11
03700 DENIA (Alicante) SPAIN
TEL.0034-965 781 218

www.bpmlighting.com