



FLORIDA

PRODUCT SHEET



REF. 10190

FEATURES

IP: 33

Installation: Surface

High: 114 mm

Light Direction: Fixed

Minimum distance to lightened objects: 0.5 m

Lamps : LED

Protection class: Class I

Indirect light: Optional

LED MODULES

Energy efficiency : A+

Driver: Included

Life time: 50.000h

LED working constant current: 700mA


Color rendering current: CRI ≥80

LED Guarantee: 5 years


FINISH

BLACK RAL 9011	WHITE RAL 9016	GOLD RAL 1036	BLUE RAL 5022	AQUA RAL 5021	GREEN RAL 6018
RED RAL 3000	FLAMINGO RAL 3018	PINK RAL 3014	ORANGE RAL 2004		

OPTIC COVER



☐ OPAL



☐ MICROPRISMATIC

DIMMABLE OPTIONS

☐ 1.10V

☐ PUSH

☐ DALI

REF		3000K/4000K
10190.01	 114 ø 450	45,6 W 4900/5000 lm
10190.02	 114 ø 650	109,2 W 11760/12000 lm
10190.03	 114 ø 950	200,2 W 21560/22000 lm
10190.04	 114 ø 1250	318,6 W 34300/35000 lm



Date: _____

Company: _____

Project: _____

Quantity: _____

Features: _____



Partida Madrigueres Sud 11
03700 DENIA (Alicante) SPAIN
TEL.0034-965 781 218

www.bpmlighting.com