



FLORIDA SQUARE

PRODUCT SHEET



REF. 10191

FEATURES

IP: 33

Installation: Pendant

High: 114 mm

Light Direction: Fixed

Minimum distance to lightened objects: 0.5 m

Lamps : LED

Protection class: Class I

Maximum cable length: 3000 mm

Indirect light: Optional

LED MODULES

Energy efficiency : A+


Driver: Included

Life time: 50.000h

LED working constant current: 700mA

Color rendering current: CRI ≥80

LED Guarantee: 5 years

REF			3000K/4000K
10191.06		27,3 W	2940/3000 lm
10191.07		54,6 W	5880/6000 lm
10191.08		109,2 W	11760/12000 lm
10191.09		218,4 W	23520/24000 lm
10191.10		364 W	39200/40000 lm



FINISH

BLACK RAL 9011	WHITE RAL 9016	GOLD RAL 1036	BLUE RAL 5022	AQUA RAL 5021	GREEN RAL 6018
RED RAL 3000	FLAMINGO RAL 3018	PINK RAL 3014	ORANGE RAL 2004		

OPTIC COVER



☐ OPAL



☐ MICROPRISMATIC

DIMMABLE OPTIONS

☐ 1.10V

☐ PUSH

☐ DALI

CONNECTION BASE

CB03





Date: _____

Company: _____

Project: _____

Quantity: _____

Features: _____



Partida Madrigueres Sud 11
03700 DENIA (Alicante) SPAIN
TEL.0034-965 781 218

www.bpmlighting.com