

m o o o i

Statistocrat Suspended Lamp

ATELIER VAN LIESHOUT



This futuristic lamp is a three-dimensional elaboration of the data structure that rule and define the city's well-being, dressed in the sleek slenderness of an efficient aluminium body. A carbon model of serious lightness, the Statistocrat Suspended Lamp is not only the perfect functional lamp, but a reminder that everything is possible if you invest your energy and knowledge in a good plan!

Detailing



Statistocrat features Joep van Lieshout's signature raw weld finish.

Colours

RAL 1004
Golden yellow

RAL 1013
Oyster white

RAL 1023
Traffic yellow

RAL 1027
Curry

RAL 2000
Yellow orange

RAL 2002
Vermilion

RAL 2004
Pure orange

RAL 3003
Ruby red

RAL 3012
Beige red

RAL 3015
Light pink

RAL 5003
Sapphire blue

RAL 5008
Grey blue

RAL 5024
Pastel blue

RAL 6010
Grass green

RAL 6021
Pale green

RAL 7001
Silver grey

RAL 7011
Iron grey

RAL 7035
Light grey

RAL 7044
Silk grey

RAL 8001
Ochre brown

RAL 8014
Sepia brown

RAL 8016
Mahogany brown

RAL 9005
Jet black


RAL 9010
Pure white

RAL 9016
Traffic white


Statistocrat Suspended Lamp

Dimensions


115cm | 45.3"



72cm | 28.3"



38cm | 14.9"



19cm | 7.5"

5cm | 2"

Product

WIDTH 115cm | 45.3"

HEIGHT 38cm | 15"

DEPTH 72cm | 28.3"

WEIGHT NETTO 15kg | 33.07lbs

Packaging

WIDTH 80cm | 31.5"

HEIGHT 45cm | 17.7"

CUBAGE 0.43m³ | 15.26ft³

LENGTH 120cm | 47.2"

WEIGHT 19.5cm | 42.99lbs

Technical CE

MATERIAL

Aluminium frame with structured matt powdercoating.

ENERGY LABEL

Energy Label B

LIGHTSOURCE TYPE

LED

NUMBER OF LIGHTSOURCES

5

INPUT VOLTAGE

220-240

MAX POWER CONSUMPTION

40W

LAMPHOLDER

LED (Solid state)

CABLE LENGTH

400cm | 157.5"

COLOUR TEMPERATUE

2700 K

LIGHT DIRECTION

All directions

INSTALLATION REQUIRED

Yes

LIGHTSOURCE INCLUDED

Yes

SHAPE

Linear

FREQUENCY

50/60

DIMMABLE

Yes

COLOUR

Black

CANOPY

Matching steel cylinder

CRI

80

LIGHT OUTPUT

1347 lm

Technical cULus

MATERIAL

Aluminium frame with structured matt powdercoating.

ENERGY LABEL

Energy Label B

INSTALLATION REQUIRED

Yes

LIGHTSOURCE TYPE

LED

NUMBER OF LIGHTSOURCES

5

INPUT VOLTAGE

100-120

MAX POWER CONSUMPTION

40W

LAMPHOLDER

LED (Solid state)

CABLE LENGTH

400cm | 157.5"

COLOUR TEMPERATUE

2700 K

LIGHT DIRECTION

All directions

LIGHTSOURCE INCLUDED

Yes

SHAPE

Linear

FREQUENCY

50/60

DIMMABLE

Yes

COLOUR

Black

CANOPY

Matching steel cylinder

CRI

80

LIGHT OUTPUT

1347 lm

Dimmer

For fluent dimming behaviour we advise a dimmer that is compatible with the following specs.
Please note the functioning of the dimmer and the power supply combination can never be predicted, it always needs to be tested in practice.

DIMMER TYPE

Mains dimmable (trailing edge / reverse phase)

LOAD TYPE

Capacitive load (C-Type)