

m o o o i

Iconic Eyes

BERNHARD DESSECKER



The first sparkle of this great idea was inspired by iconic automotive headlights. They have been modified to design a grand pendant light with a classy, powerful impact for the foyer of the Bavarian National Museum in Germany. The light's oval design is modern with a classic touch. It generates a precious ambient glow enhanced by bright rings of light and is produced in two sizes. Glorious and breathtaking in appearance, it consists of numerous lenses and a constellation of LED lights.

Detailing



Iconic Eyes consists of the characteristic headlights of a BMW MINI, which are placed in an oval shape and create an atmospheric glow.

Colours

Black Chrome

Iconic Eyes Iconic Eyes 161

Dimensions

77cm | 30.3"



119cm | 46.9"

Product

WIDTH 77cm | 30.3"
HEIGHT 119cm | 46.9"
DEPTH 77cm | 30.3"
DIAMETER 77cm | 30.3"
WEIGHT NETTO 70kg |
154.32lbs

Packaging

WIDTH 96cm | 37.8"
HEIGHT 164cm | 64.6"
CUBAGE 1.51m³ | 53.38ft³
LENGTH 96cm | 37.8"
WEIGHT 100cm | 220.46lbs

Technical CE

MATERIAL

PE Sphere with PC and ABS lenses and chrome detailing

ENERGY LABEL

Energy Label B

LIGHTSOURCE INCLUDED

Yes

SHAPE

Abstract

FREQUENCY

50/60

DIMMABLE

Yes

COLOUR

Transparent with tinned cores

CANOPY

White metal rectangle

CRI

88

LIGHTSOURCE TYPE

LED

NUMBER OF LIGHTSOURCES

161

INPUT VOLTAGE

100-264

MAX POWER CONSUMPTION

220W

LAMPHOLDER

LED (Solid state)

CABLE LENGTH

1000cm | 393.7"

COLOUR TEMPERATUE

2700 K

LIGHT OUTPUT

7019 lm

Technical cULus

MATERIAL

PE Sphere with PC and ABS lenses and chrome detailing

ENERGY LABEL

Energy Label B

LIGHTSOURCE TYPE

LED

LIGHTSOURCE INCLUDED

Yes

SHAPE

Abstract

FREQUENCY

50/60

DIMMABLE

Yes

COLOUR

Transparent with tinned cores

CANOPY

White metal rectangle

CRI

88

NUMBER OF LIGHTSOURCES

161

INPUT VOLTAGE

100-264

MAX POWER CONSUMPTION

220W

LAMPHOLDER

LED (Solid state)

CABLE LENGTH

1000cm | 393.7"

COLOUR TEMPERATUE

2700 K

LIGHT OUTPUT

7019 lm

Iconic Eyes Iconic Eyes 85

Dimensions

60cm | 23.6"



88cm | 34.6"

Product

WIDTH 60cm | 23.6"

HEIGHT 88cm | 34.6"

DEPTH 60cm | 23.6"

DIAMETER 60cm | 23.6"

WEIGHT NETTO 35kg | 77.16lbs

Packaging

WIDTH 86cm | 33.9"

HEIGHT 136cm | 53.5"

CUBAGE 1.01m³ | 35.52ft³

LENGTH 86cm | 33.9"

WEIGHT 90cm | 198.42lbs

Technical CE

MATERIAL

PE Sphere with PC and ABS lenses and chrome detailing

ENERGY LABEL

Energy Label B

LIGHTSOURCE INCLUDED

Yes

SHAPE

Abstract

LIGHTSOURCE TYPE

LED

NUMBER OF LIGHTSOURCES

85

INPUT VOLTAGE

100-264

FREQUENCY

50/60

DIMMABLE

Yes

COLOUR

Transparent with tinned cores

CANOPY

White metal rectangle

CRI

88

MAX POWER CONSUMPTION

110W

LAMPHOLDER

LED (Solid state)

CABLE LENGTH

400cm | 157.5"

COLOUR TEMPERATUE

2700 K

LIGHT OUTPUT

3706 lm

*Technical cULus***MATERIAL**

PE Sphere with PC and ABS lenses and chrome detailing

ENERGY LABEL

Energy Label B

LIGHTSOURCE INCLUDED

Yes

SHAPE

Abstract

FREQUENCY

50/60

DIMMABLE

Yes

COLOUR

Transparent with tinned cores

CANOPY

White metal rectangle

CRI

88

LIGHTSOURCE TYPE

LED

NUMBER OF LIGHTSOURCES

85

INPUT VOLTAGE

100-264

MAX POWER CONSUMPTION

110W

LAMPHOLDER

LED (Solid state)

CABLE LENGTH

400cm | 157.5"

COLOUR TEMPERATUE

2700 K

LIGHT OUTPUT

3706 lm

Dimmer

For fluent dimming behaviour we advise a dimmer that is compatible with the following specs.

DIMMER TYPE

1-10V

Please note the functioning of the dimmer and the power supply combination can never be predicted, it always needs to be tested in practice.

