

m o o o i

Flock of Light

STUDIO TOER



Flock of Light is an (art) installation that is developed to be a lighting product in a size that fits your home. Inspired by the organic form and dynamism of a swarm of fireflies, Flock of Light mimicks a natural nocturnal phenomenon that will evoke sensations wherever it settles.

Flock of Light Flock of Light 11

Dimensions

80cm | 31.5"



65cm | 25.6"

65cm | 25.6"



Product

WIDTH 80cm | 31.5"

HEIGHT 65cm | 25.6"

DEPTH 65cm | 25.6"

WEIGHT NETTO 0.9kg | 1.98lbs

Technical CE

MATERIAL

Brass and bronze with plastic diffusers

ENERGY LABEL

Energy Label A+

LIGHTSOURCE TYPE

LED

NUMBER OF LIGHTSOURCES

11

INPUT VOLTAGE

220-240

MAX POWER CONSUMPTION

13W

LAMPHOLDER

LED (Solid state)

CABLE LENGTH

250cm | 98.4"

COLOUR TEMPERATUE

2700 K

LIGHT DIRECTION

All directions

INSTALLATION REQUIRED

Yes

LIGHTSOURCE INCLUDED

Yes

SHAPE

Abstract

FREQUENCY

50/60

DIMMABLE

Yes

COLOUR

Transparent with tinned cores

CANOPY

Pebble II White, ABS

CRI

91

LIGHT OUTPUT

1240 lm

*Technical cULus***MATERIAL**

Brass and bronze with plastic diffusers

ENERGY LABEL

Energy Label A+

LIGHTSOURCE TYPE

LED

NUMBER OF LIGHTSOURCES

11

INPUT VOLTAGE

110-130

MAX POWER CONSUMPTION

13W

LAMPHOLDER

LED (Solid state)

CABLE LENGTH

250cm | 98.4"

COLOUR TEMPERATUE

2700 K

INSTALLATION REQUIRED

Yes

LIGHTSOURCE INCLUDED

Yes

SHAPE

Abstract

FREQUENCY

50/60

DIMMABLE

Yes

COLOUR

Transparent with tinned cores

CANOPY

Pebble II White, ABS

CRI

91

LIGHT DIRECTION

All directions

LIGHT OUTPUT

1240 lm

Flock of Light Flock of Light 21

Dimensions

135cm | 53.2"



80cm | 31.5"

85cm | 33.5"



Product

WIDTH 135cm | 53.1"

HEIGHT 65cm | 25.6"

DEPTH 85cm | 33.5"

WEIGHT NETTO 1.4kg | 3.09lbs

Technical CE

MATERIAL

Brass and bronze with plastic diffusers

ENERGY LABEL

Energy Label A+

LIGHTSOURCE TYPE

LED

NUMBER OF LIGHTSOURCES

21

INPUT VOLTAGE

220-240

MAX POWER CONSUMPTION

23W

LAMPHOLDER

LED (Solid state)

CABLE LENGTH

250cm | 98.4"

COLOUR TEMPERATUE

2700 K

LIGHT DIRECTION

All directions

INSTALLATION REQUIRED

Yes

LIGHTSOURCE INCLUDED

Yes

SHAPE

Abstract

FREQUENCY

50/60

DIMMABLE

Yes

COLOUR

Transparent with tinned cores

CANOPY

Pebble II White, ABS

CRI

91

LIGHT OUTPUT

2308 lm

Technical cULus

MATERIAL

Brass and bronze with plastic diffusers

ENERGY LABEL

Energy Label A+

LIGHTSOURCE TYPE

LED

NUMBER OF LIGHTSOURCES

21

INPUT VOLTAGE

110-130

MAX POWER CONSUMPTION

23W

LAMPHOLDER

LED (Solid state)

CABLE LENGTH

250cm | 98.4"

COLOUR TEMPERATUE

2700 K

LIGHT DIRECTION

All directions

INSTALLATION REQUIRED

Yes

LIGHTSOURCE INCLUDED

Yes

SHAPE

Abstract

FREQUENCY

50/60

DIMMABLE

Yes

COLOUR

Transparent with tinned cores

CANOPY

Pebble II White, ABS

CRI

91

LIGHT OUTPUT

2308 lm

Dimmer

For fluent dimming behaviour we advise a dimmer that is compatible with the following specs.

Please note the functioning of the dimmer and the power supply combination can never be predicted, it always needs to be tested in practice.

DIMMER TYPE

Mains dimmable (trailing edge / reverse phase)

LOAD TYPE

Capacitive load (C-Type)
