moooi





An elegant, bright, lighthearted bubble is dressed in a fine web of white or black thread that shines and glimmers in the light. Thanks to an integrated LED lamp, this new creation by Bertjan Pot subtly diffuses its soft, magic glow around the room.

Detailing



The NR2 features a branded light diffuser that subtly diffuses its soft, magic glow around the room.

Colours




White

Black

NR2

Dimensions

55cm | 21.7"



Product

width 55cm | 21.7" неight 40cm | 15.7" depth 55cm | 21.7" diameter 55cm | 21.7" weight netto 4kg | 8.82lbs

Packaging

width 57 cm | 22.4"Height 52 cm | 20.5"Cubage $0.17 \text{ m}^3 | 5.97 \text{ ft}^3$ Length 57 cm | 22.4"weight 3.7 cm | 8.16 lbs

Technical CE

MATERIAL

Ellipsoid from fiberglass with epoxy resin, ABS cover, PC diffuser and aluminum heatsink

ENERGY LABEL	INSTALLATION REQUIRED
Energy Label B	Yes
LIGHTSOURCE TYPE	LIGHTSOURCE INCLUDED
LED	Yes
NUMBER OF LIGHTSOURCES	SHAPE
1	Oval
INPUT VOLTAGE	FREQUENCY
208-277	50/60
MAX POWER CONSUMPTION	DIMMABLE
12W	Yes
LAMPHOLDER	COLOUR
LED (Solid state)	Black
CABLE LENGTH	CANOPY
400cm 157.5"	NR2 Canopy Black
COLOUR TEMPERATUE	CRI
2700 K	82
LIGHT DIRECTION	LIGHT OUTPUT
All directions	450 lm

Technical cULus

MATERIAL

Ellipsoid from fiberglass with epoxy resin, ABS cover, PC diffuser and aluminum heatsink

ENERGY LABEL	INSTALLATION REQUIRED
Energy Label B	Yes
LIGHTSOURCE TYPE	LIGHTSOURCE INCLUDED
LED	Yes
NUMBER OF LIGHTSOURCES	SHAPE Oval
INPUT VOLTAGE	FREQUENCY
120	50/60
MAX POWER CONSUMPTION	DIMMABLE
12W	Yes
LAMPHOLDER	COLOUR
LED (Solid state)	Black
CABLE LENGTH	сапору
400cm 157.5"	NR2 Canopy Black
COLOUR TEMPERATUE	CRI
2700 K	82
LIGHT DIRECTION	LIGHT OUTPUT
All directions	450 lm

Dimmer

For fluent dimming behaviour we advise a dimmer that is compatible with the following specs. Please note the functioning of the dimmer and the

power supply combination can never be predicted, it always needs to be tested in practice.

DIMMER TYPE

Mains dimmable (trailing edge / reverse phase)

LOAD TYPE

Capacitive load (C-Type)