

m o o o i

# Plant Chandelier

KRANEN/GILLE



The philosophy behind the Plant Chandelier, designed by Kranen/Gille, is the imitation of nature's structures while indulging in the poetry of their beauty. Inspired by the linear patterns of Karl Blossfeldt's plant photography, and unrestricted by cables or wires, the Plant Chandelier is free to elegantly bloom towards the ceiling. Its silhouette follows the anatomy of sun-kissed tree branches, with a golden glow, which converges into frosted domes of light.

---

## *Detailing*



The Plant Chandelier captivates the architectural uniformity in nature's design, with its branches that grow and spread in definite directions.

---

## *Colours*






Brass

---

## *Plant Chandelier*

Dimensions

90cm | 35.4"



Product

**WIDTH** 90cm | 35.4"

**HEIGHT** 80cm | 31.5"

**DEPTH** 78cm | 30.7"

**WEIGHT NETTO** 20kg |

44.09lbs

Packaging

**WIDTH** 92cm | 36.2"

**HEIGHT** 91cm | 35.8"

**CUBAGE** 0.84m<sup>3</sup> | 29.57ft<sup>3</sup>

**LENGTH** 100cm | 39.4"

**WEIGHT** 27.5cm | 60.63lbs

Technical CE

**MATERIAL**

Steel frame, glass diffusers

**ENERGY LABEL**

**LIGHTSOURCE TYPE**

LED

**LIGHTSOURCE INCLUDED**

Yes

**NUMBER OF LIGHTSOURCES**

8

**INPUT VOLTAGE**

220-240

**FREQUENCY**

50/60

**MAX POWER CONSUMPTION**

16W

**DIMMABLE**

Yes

**LAMPHOLDER**

LED (Solid state)

**COLOUR**

Transparent with tinned cores

**CABLE LENGTH**

400cm | 157.5"

**CANOPY**

Matching steel cylinder

**COLOUR TEMPERATUE**

2700 K

**CRI**

80

**LIGHT DIRECTION**

All directions

**LIGHT OUTPUT**

1318 lm

**EEI**

0.17

**EFFICIENCY**

82.38 lm/W

Technical cULus

**MATERIAL**

Steel frame, glass diffusers

**ENERGY LABEL**

<b>LIGHTSOURCE INCLUDED</b>	<b>LIGHTSOURCE TYPE</b>
Yes	LED
<b>INPUT VOLTAGE</b>	<b>NUMBER OF LIGHTSOURCES</b>
110-130	8
<b>MAX POWER CONSUMPTION</b>	<b>FREQUENCY</b>
16W	50/60
<b>LAMPHOLDER</b>	<b>DIMMABLE</b>
LED (Solid state)	Yes
<b>CABLE LENGTH</b>	<b>COLOUR</b>
400cm   157.5"	Transparent with tinned cores
<b>COLOUR TEMPERATUE</b>	<b>CANOPY</b>
2700 K	Matching steel cylinder
<b>LIGHT DIRECTION</b>	<b>CRI</b>
All directions	80
<b>EEI</b>	<b>LIGHT OUTPUT</b>
0.17	1318 lm
	<b>EFFICIENCY</b>
	82.38 lm/W

---

## *Dimmer*

For fluent dimming behaviour we advise a dimmer that is compatible with the following specs.  
Please note the functioning of the dimmer and the power supply combination can never be predicted, it always needs to be tested in practice.

<b>DIMMER TYPE</b>
Mains dimmable (trailing edge / reverse phase)
<b>LOAD TYPE</b>
Capacitive load (C-Type)

---