

# ZIRKOL – S PLUS

ZIRKOL -S Plus is a family of square suspension lamps suitable for general and decorative lighting.

Anodized aluminium body and opal screen to a homogeneous lighting. CRI > 80

Light emission can be direct light and double light emission with high flux and different colour temperatures.

Remote driver included



## 1X1M | DOWNLIGHT - 3000K - HIGH FLUX

---

### LAMPING

Source	Linear LED
Total power	75W
Emission	Diffused orientable
Tension	24VDC
Color temperature	3000K
Luminous flux	7600lm
Initial luminaire efficacy	100lm/W
Typ CRI	> 80
Energy class	A+
IP class	40
Dimensions	100x100x5cm
Materials	Aluminium
Ambient temperature range	0°C / 35°
Performance ambient temperature	25°
Notes	remote driver included; suspension kit included; cable 5m; optional controls: DALI, DMX, Casambi
Customization options	Shapes, sizes
Net lamp weight	5,7 kg

### Codes

PZRS0310G15WNE


### Structure

black

### PACKAGE

Package 01      Dimension: 105x105x5 cm / Gross weight: 9,12 kg

### Certificazioni



## 1X1M | DOWNLIGHT - 3000K - DALI - HIGH FLUX

---

### LAMPING

Source	Linear LED
Total power	75W
Emission	Diffused orientable
Switching	DALI
Tension	24VDC
Color temperature	3000K
Luminous flux	7600lm
Initial luminaire efficacy	80lm/W
Typ CRI	> 80
Energy class	A+
IP class	40
Dimensions	100x100x5cm
Materials	Aluminium
Ambient temperature range	0°C / 35°
Performance ambient temperature	25°
Notes	remote driver and DALI interface included; suspension kit included; cable 5m; optional controls: DMX, Casambi
Customization options	Shapes, sizes
Net lamp weight	5,7 kg

### Codes

PZRS1610G15WNE


### Structure

black

### PACKAGE

Package 01      Dimension: 105x105x5 cm / Gross weight: 9,12 kg

### Certificazioni



## 1X1M | UP - DOWNLIGHT - 3000K - HIGH FLUX

---

### LAMPING

Source	Linear LED
Total power	150W
Emission	Diffused orientable
Tension	24VDC
Color temperature	3000K
Luminous flux	4800lm + 7600lm
Initial luminaire efficacy	80lm/W
Typ CRI	> 80
Energy class	A+
IP class	40
Dimensions	100x100x5cm
Materials	Aluminium
Ambient temperature range	0°C / 35°
Performance ambient temperature	25°
Notes	remote driver included; suspension kit included; cable 5m; optional controls: DALI, DMX, Casambi
Customization options	Shapes, sizes
Net lamp weight	5,7 kg

### Codes

PZRS1410G15WNE


### Structure

black

### PACKAGE

Package 01      Dimension: 105x105x5 cm / Gross weight: 9,12 kg

### Certificazioni



## 1X1M | UP - DOWNLIGHT - 3000K - DALI - HIGH FLUX

---

### LAMPING

Source	Linear LED
Total power	150W
Emission	Diffused orientable
Switching	DALI
Tension	24VDC
Color temperature	3000K
Luminous flux	4800lm + 7600lm
Initial luminaire efficacy	100lm/W
Typ CRI	> 80
Energy class	A+
IP class	40
Dimensions	100x100x5cm
Materials	Aluminium
Ambient temperature range	0°C / 35°
Performance ambient temperature	25°
Notes	remote driver and DALI interface included; suspension kit included; cable 5m; optional controls: DMX, Casambi
Customization options	Shapes, sizes
Net lamp weight	5,7 kg

### Codes

PZRS1710G15WNE


### Structure

black

### PACKAGE

Package 01 Dimension: 105x105x5 cm / Gross weight: 9,12 kg

### Certificazioni



## 1X1M | DOWNLIGHT - 4000K - HIGH FLUX

---

### LAMPING

Source	Linear LED
Total power	75W
Emission	Diffused orientable
Tension	24VDC
Color temperature	4000K
Luminous flux	7600lm
Initial luminaire efficacy	100lm/W
Typ CRI	> 80
Energy class	A+
IP class	40
Dimensions	100x100x5cm
Materials	Aluminium
Ambient temperature range	0°C / 35°
Performance ambient temperature	25°
Notes	remote driver included; suspension kit included; cable 5m; optional controls: DALI, DMX, Casambi
Customization options	Shapes, sizes
Net lamp weight	5,7 kg

### Codes

PZRS0310G15NNE


### Structure

black

### PACKAGE

Package 01      Dimension: 105x105x5 cm / Gross weight: 9,12 kg

### Certificazioni



## 1X1M | DOWNLIGHT - 4000K - DALI - HIGH FLUX

---

### LAMPING

Source	Linear LED
Total power	75W
Emission	Diffused orientable
Switching	DALI
Tension	24VDC
Color temperature	4000K
Luminous flux	7600lm
Initial luminaire efficacy	80lm/W
Typ CRI	> 80
Energy class	A+
IP class	40
Dimensions	100x100x5cm
Materials	Aluminium
Ambient temperature range	0°C / 35°
Performance ambient temperature	25°
Notes	remote driver and DALI interface included; suspension kit included; cable 5m; optional controls: DMX, Casambi
Customization options	Shapes, sizes
Net lamp weight	5,7 kg

### Codes

PZRS1610G15NNE


### Structure

black

### PACKAGE

Package 01      Dimension: 105x105x5 cm / Gross weight: 9,12 kg

### Certificazioni



## 1X1M | UP - DOWNLIGHT - 4000K - HIGH FLUX

---

### LAMPING

Source	Linear LED
Total power	150W
Emission	Diffused orientable
Tension	24VDC
Color temperature	4000K
Luminous flux	4800lm + 7600lm
Initial luminaire efficacy	80lm/W
Typ CRI	> 80
Energy class	A+
IP class	40
Dimensions	100x100x5cm
Materials	Aluminium
Ambient temperature range	0°C / 35°
Performance ambient temperature	25°
Notes	remote driver included; suspension kit included; cable 5m; optional controls: DALI, DMX, Casambi
Customization options	Shapes, sizes
Net lamp weight	5,7 kg

### Codes

PZRS1410G15NNE


### Structure

black

### PACKAGE

Package 01 Dimension: 105x105x5 cm / Gross weight: 9,12 kg

### Certificazioni





## 1X1M | UP - DOWNLIGHT - 4000K - DALI - HIGH FLUX

---

### LAMPING

Source	Linear LED
Total power	150W
Emission	Diffused orientable
Switching	DALI
Tension	24VDC
Color temperature	4000K
Luminous flux	4800lm + 7600lm
Initial luminaire efficacy	100lm/W
Typ CRI	> 80
Energy class	A+
IP class	40
Dimensions	100x100x5cm
Materials	Aluminium
Ambient temperature range	0°C / 35°
Performance ambient temperature	25°
Notes	remote driver and DALI interface included; suspension kit included; cable 5m; optional controls: DMX, Casambi
Customization options	Shapes, sizes
Net lamp weight	5,7 kg

### Codes

PZRS1710G15NNE


### Structure

black

### PACKAGE

Package 01 Dimension: 105x105x5 cm / Gross weight: 12,06 kg

### Certificazioni



## 1,5X1,5M | DOWNLIGHT - 3000K - HIGH FLUX

---

### LAMPING

Source	Linear LED
Total power	112,5W
Emission	Diffused orientable
Tension	24VDC
Color temperature	3000K
Luminous flux	11000lm
Initial luminaire efficacy	100lm/W
Typ CRI	> 80
Energy class	A+
IP class	40
Dimensions	150x150x5cm
Materials	Aluminium
Ambient temperature range	0°C / 35°
Performance ambient temperature	25°
Notes	remote driver included; suspension kit included; cable 5m; optional controls: DALI, DMX, Casambi
Customization options	Shapes, sizes
Net lamp weight	8,56 kg

### Codes

PZRS0315G15WNE


### Structure

black

### PACKAGE

Package 01 Dimension: 155x155x5 cm / Gross weight: 12,06 kg

### Certificazioni



## 1,5X1,5M | DOWNLIGHT - 3000K - DALI - HIGH FLUX

### LAMPING

Source	Linear LED
Total power	112,5W
Emission	Diffused orientable
Switching	DALI
Tension	24VDC
Color temperature	3000K
Luminous flux	11000lm
Initial luminaire efficacy	82lm/W
Typ CRI	> 80
Energy class	A+
IP class	40
Dimensions	150x150x5cm
Materials	Aluminium
Ambient temperature range	0°C / 35°
Performance ambient temperature	25°
Notes	remote driver and DALI interface included; suspension kit included; cable 5m; optional controls: DMX, Casambi
Customization options	Shapes, sizes
Net lamp weight	8,56 kg

### Codes

PZRS1615G15WNE


### Structure

black

### PACKAGE

Package 01 Dimension: 155x155x5 cm / Gross weight: 12,06 kg

### Certificazioni



## 1,5X1,5M | UP - DOWNLIGHT - 3000K - HIGH FLUX

---

### LAMPING

Source	Linear LED
Total power	225W
Emission	Diffused orientable
Tension	24VDC
Color temperature	3000K
Luminous flux	7200lm + 11000lm
Initial luminaire efficacy	82lm/W
Typ CRI	> 80
Energy class	A+
IP class	40
Dimensions	150x150x5cm
Materials	Aluminium
Ambient temperature range	0°C / 35°
Performance ambient temperature	25°
Notes	remote driver included; suspension kit included; cable 5m; optional controls: DALI, DMX, Casambi
Customization options	Shapes, sizes
Net lamp weight	8,56 kg

### Codes

PZRS1415G15WNE


### Structure

black

### PACKAGE

Package 01      Dimension: 155x155x5 cm / Gross weight: 12,06 kg

### Certificazioni



## 1,5X1,5M | UP - DOWNLIGHT - 3000K - DALI - HIGH FLUX

---

### LAMPING

Source	Linear LED
Total power	225W
Emission	Diffused orientable
Switching	DALI
Tension	24VDC
Color temperature	3000K
Luminous flux	7200lm + 11000lm
Initial luminaire efficacy	100lm/W
Typ CRI	> 80
Energy class	A+
IP class	40
Dimensions	150x150x5cm
Materials	Aluminium
Ambient temperature range	0°C / 35°
Performance ambient temperature	25°
Notes	remote driver and DALI interface included; suspension kit included; cable 5m; optional controls: DMX, Casambi
Customization options	Shapes, sizes
Net lamp weight	8,56 kg

### Codes

PZRS1715G15WNE


### Structure

black

### PACKAGE

Package 01 Dimension: 155x155x5 cm / Gross weight: 12,06 kg

### Certificazioni



## 1,5X1,5M | DOWNLIGHT - 4000K - HIGH FLUX

---

### LAMPING

Source	Linear LED
Total power	112,5W
Emission	Diffused orientable
Tension	24VDC
Color temperature	4000K
Luminous flux	11000lm
Initial luminaire efficacy	100lm/W
Typ CRI	> 80
Energy class	A+
IP class	40
Dimensions	150x150x5cm
Materials	Aluminium
Ambient temperature range	0°C / 35°
Performance ambient temperature	25°
Notes	remote driver included; suspension kit included; cable 5m; optional controls: DALI, DMX, Casambi
Customization options	Shapes, sizes
Net lamp weight	8,56 kg

### Codes

PZRS0315G15NNE


### Structure

black

### PACKAGE

Package 01 Dimension: 155x155x5 cm / Gross weight: 12,06 kg

### Certificazioni



## 1,5X1,5M | DOWNLIGHT - 4000K - DALI - HIGH FLUX

---

### LAMPING

Source	Linear LED
Total power	112,5W
Emission	Diffused orientable
Switching	DALI
Tension	24VDC
Color temperature	4000K
Luminous flux	11000lm
Initial luminaire efficacy	82lm/W
Typ CRI	> 80
Energy class	A+
IP class	40
Dimensions	150x150x5cm
Materials	Aluminium
Ambient temperature range	0°C / 35°
Performance ambient temperature	25°
Notes	remote driver and DALI interface included; suspension kit included; cable 5m; optional controls: DMX, Casambi
Customization options	Shapes, sizes
Net lamp weight	8,56 kg

### Codes

PZRS1615G15NNE


### Structure

black

### PACKAGE

Package 01 Dimension: 155x155x5 cm / Gross weight: 12,06 kg

### Certificazioni



## 1,5X1,5M | UP - DOWNLIGHT - 4000K - HIGH FLUX

---

### LAMPING

Source	Linear LED
Total power	225W
Emission	Diffused orientable
Tension	24VDC
Color temperature	4000K
Luminous flux	7200lm + 11000lm
Initial luminaire efficacy	82lm/W
Initial chromaticity	SDCM < 3
Typ CRI	> 80
Energy class	A+
IP class	40
Dimensions	150x150x5cm
Materials	Aluminium
Ambient temperature range	20°C / 35°
Performance ambient temperature	25°
Notes	remote driver included; suspension kit included; cable 5m; optional controls: DALI, DMX, Casambi
Customization options	Shapes, sizes, colour temperatures, RGB, RGBW
Net lamp weight	8,56 kg

### Codes

PZRS1415G15NNE


### Structure

black

### PACKAGE

Package 01 Dimension: 155x155x5 cm / Gross weight: 12,06 kg

### Certificazioni





## 1,5X1,5M | UP - DOWNLIGHT - 4000K - DALI - HIGH FLUX

### LAMPING

Source	Linear LED
Total power	225W
Emission	Diffused orientable
Switching	DALI
Tension	24VDC
Color temperature	4000K
Luminous flux	7200lm + 11000lm
Initial luminaire efficacy	100lm/W
Initial chromaticity	SDCM < 3
Typ CRI	> 80
Energy class	A+
IP class	40
Dimensions	150x150x5cm
Materials	Aluminium
Ambient temperature range	20°C / 35°
Performance ambient temperature	25°
Notes	remote driver and DALI interface included; suspension kit included; cable 5m; optional controls: DMX, Casambi
Customization options	Shapes, sizes, colour temperatures, RGB, RGBW
Net lamp weight	8,56 kg

### Codes

PZRS1715G15NNE

### Structure

black

### PACKAGE

Package 01 Dimension: 155x155x5 cm / Gross weight: 1,25 kg

### Certificazioni

